



doucette
industries, inc


Item # AC 200-2(C), AC Series Mechanically Cleanable Desuperheaters (5 to 200 tons)

Heats Hot Water Utilizing Waste Heat from Refrigeration,
Air Conditioners and Heat Pump Systems

The Doucette AC Series Substantially Reduces Your Hot
Water Heating Costs

- Heats potable water up to 140 °F using waste heat
- Typical Payback Period of Two Years or Less
- Reduces A/C operating costs 5% to 10%
- Mechanical Cleanable Counterflow Design
- Compact and Ready to Install
- Works with All Major Manufacturers' Systems

The Doucette AC Series™ heat recovery unit delivers substantial energy savings by heating potable water by recovering waste heat from refrigeration, air conditioning and heat pump systems. The AC Series™ can effectively heat water up to 140°F, and is ideal for systems ranging from 5 - 200 HP using reciprocating, scroll and screw compressors. The unit arrives as a standard factory package that is ready to install, and can be applied to both air- and water-cooled systems using.



Call dii

Specifications

TR	200 tons	
Typical Applications	<ul style="list-style-type: none"> • Domestic Hot Water • Heating • Process Water Heating • Space Heating • Pool Heating • Hot Deck Reheat • Sub-Soil Heating 	<ul style="list-style-type: none"> • Restaurants • Hotels/Motels • Hospitals • Schools • Food Processing • Ice Rinks • Dormitories



20 Leigh Drive,
York, Pennsylvania 17406-8474



Website: www.doucetteindustries.com



Phone: 717-845-8746
Toll-free: 800-445-7511
Fax: 717-845-2864




Commercial/Industrial: AdamM@doucetteindustries.com
Residential/Light Commercial: AdamM@doucetteindustries.com



# Circuits	2
Cleanability	Mechanical
Refrig. Conn.	3 1/8" OD
Water Conn.	2 5/8" OD
Length	52 1/2 "
Width	42 3/4 "
Height	25-13/16 "
Weight	1400 lbs

Mechanical Specifications	
Optional Pump	Grundfos UP43-75BF, Circulating Pump (\$1,630.00)
Heat Exchanger	Mechanically cleanable, vented double wall, U.L. & USDA Listed, 450 psig side DWP shell (optional 600 psig), 300 psig tube side DWP with removable cleanout fittings
Cabinet	20 Gauge, 0.040" painted aluminum with removable back panel and 1" fiberboard insulation.





DESIGN PRESSURE:
SHELLSIDE 450PSIG
TUBESIDE 300PSIG

TOLERANCES	SCALE	DRAWN BY:	MLB
DECIMAL ± .125	.078125	APP. BY:	RJR
FRACTIONAL ±	TITLE	AC 200-2 (C) HP	
ANGULAR ±	DATE	11/17/99	DRAWING NUMBER 96122
GAUGE 20	ALL DIMENSIONS INCHES, UNLESS SPECIFIED		

- CONNECTIONS:
- 1.) REFRIGERANT SUPPLY, #1 3-1/8" OD COPPER SWEAT
 - 2.) REFRIGERANT RETURN, #1 3-1/8" OD COPPER SWEAT
 - 3.) REFRIGERANT SUPPLY, #2 3-1/8" OD COPPER SWEAT
 - 4.) REFRIGERANT RETURN, #2 3-1/8" OD COPPER SWEAT
 - 5.) WATER RETURN 2-5/8" OD COPPER SWEAT
 - 6.) WATER SUPPLY 2-5/8" OD COPPER SWEAT
- 49.25 X 42.75 X 20.5



20 Leigh Drive,
York, Pennsylvania 17406-8474



Website: www.doucetteindustries.com



Phone: 717-845-8746
Toll-free: 800-445-7511
Fax: 717-845-2864



Commercial/Industrial: AdamM@doucetteindustries.com
Residential/Light Commercial: AdamM@doucetteindustries.com